



Envirotech Accent Dimout Blind Fabric

“Intelligent Blind Fabrics, Protecting You and The Environment.”

This fabric features a smooth, uncoated finish that creates a sleek and stylish dimout effect. Designed for areas where fire resistance is not required, it offers excellent light shading and privacy. Available in 40 colours and multiple widths—including 89mm, 2000mm, and 2500mm—it suits a wide range of window sizes and applications.

The fabric is moisture resistant and incorporates Biosafe®, an internationally recognised antimicrobial treatment tested to meet rigorous infection control standards.





Accent Dimout Non-Flame Retardant

Presenting 40 colours and a choice of fabric widths, this dimout fabric with Biosafe® accreditation is ideal for commercial, educational and healthcare environments. It provides effective privacy and light shading while supporting hygiene through its proven antimicrobial formula.

With its versatility and durability, this fabric is perfect for projects requiring a combination of style, comfort and infection control.



Fabric Composition:	100% Polyester
Fabric Range:	40
Louvre Widths:	89mm (3.5")
Vertical Roll Length:	100m
Roller Fabric Width:	2000mm / 2500mm
Roller Fabric Length:	30m
Fabric Thickness:	0.3mm
Fabric Weight:	220 g/m2
Shading:	Dimout
Moisture Resistance:	Suitable for moist conditions
Anti-Bacterial:	Incorporates Biosafe® formula



More fabric colours and
data tables overleaf...

Accent Dimout Non-Flame Retardant

89 – 2500 nm	HT %	LT %	UP %	LA %	HR %	LR %	SC	GTOT
Vanilla	13	10	90	13	73	77	0.35	0.29
Tan	9	1	100	34	56	42	0.44	0.37
Linen	12	7	100	18	70	71	0.36	0.30
Stone	6	3	100	47	48	50	0.48	0.41
Sandstone	13	9	100	16	71	74	0.36	0.30
Warm Almond	12	8	90	16	71	73	0.35	0.30
Rose	13	6	100	33	67	61	0.39	0.33
Dusty Pink	11	3	100	45	63	52	0.41	0.35
Smokey Mauve	9	1	100	67	51	32	0.47	0.40
Chocolate	1	0	100	87	14	13	0.68	0.58
Pink	12	2	100	74	54	24	0.46	0.39
Lilac	11	2	100	61	58	37	0.44	0.37
Heather	9	1	100	31	60	43	0.41	0.35
Plum	9	0	100	90	44	10	0.52	0.44
Tangerine	11	2	100	72	51	26	0.48	0.41
Scarlet	7	1	100	84	41	15	0.53	0.45
Cherry	4	<1	100	62	34	16	0.56	0.47
Berry	2	0	100	91	23	9	0.62	0.53
Apple	4	1	100	54	42	42	0.52	0.44
Primrose	13	9	100	18	68	73	0.38	0.32



HT % : Heat Transmittance
 LT % : Light Transmittance
 UP % : Ultraviolet Protection
 LA % : Light Absorption
 HR % : Heat Reflection
 LR % : Light Reflection
 SC : Shading Co-Efficiency
 GTOT : Total Value of Solar Energy

Accent Dimout Non-Flame Retardant

	89 – 3000 nm	HT %	LT %	UP %	LA %	HR %	LR %	SC	GTOT
Sunshine		12	5	100	38	59	57	0.44	0.37
Mustard		11	11	100	23	66	66	0.54	0.39
Marsh		9	1	100	76	43	23	0.52	0.44
Lawn		<1	<1	100	80	20	19	0.64	0.54
Pine Green		8	0	100	86	37	14	0.55	0.47
Turquoise		8	1	100	71	46	28	0.51	0.43
Aqua		9	1	100	70	47	29	0.49	0.42
Mist		5	3	100	41	54	56	0.44	0.38
Surf		11	4	100	26	63	55	0.40	0.34
Marine		1	<1	100	70	28	19	0.59	0.50
Cobalt		6	0	100	59	35	10	0.56	0.47
Dark Azure		0	0	100	89	11	7	0.69	0.59
Sesame		13	12	100	10	77	82	0.32	0.28
Frost		14	12	100	9	78	84	0.32	0.27
Ash		11	3	100	45	61	52	0.42	0.36
Stone Grey		2	1	100	56	41	42	0.51	0.44
Fossil Grey		<1	1	100	23	27	28	0.71	0.61
Graphite		<1	0	100	82	18	19	0.65	0.55
Steel		0	0	100	89	11	12	0.69	0.59
Coal		0	0	100	94	6	6	0.72	0.61



HT % : Heat Transmittance
 LT % : Light Transmittance
 UP % : Ultraviolet Protection
 LA % : Light Absorption
 HR % : Heat Reflection
 LR % : Light Reflection
 SC : Shading Co-Efficiency
 GTOT : Total Value of Solar Energy